

OK TO ENTER /K.Y./ 1/12/2010
---------------------------------

*IN THE CLAIMS*

1. (Currently Amended) A method for analyzing a media path in a packet switched network, comprising:

conducting an initial media call signaling session with logic circuitry for establishing a media call and setting up the media path over the packet switched network, the media path established by successful completion of the initial media call signaling setup session and used for receiving or transmitting media packets containing media payloads;

sending and/or receiving one or more no-op media payload packets over the media path with the logic circuitry during and within the initial media call signaling session prior to establishing the media call and setting up the media path, the no-op media payload packets formatted as though the media packets contain media payloads but the no-op media payload packets formatted without media payloads and not containing media payloads;

requesting or receiving media path quality information with the logic circuitry associated with the no-op media payload packets during the initial media call signaling session prior to establishment of the media call being established by the initial media call signaling session;

selectively completing or terminating the initial media call signaling session with the logic circuitry according to the information obtained from the transmission of the no-op media payload packet during the initial media call signaling session, successful completion of the initial media call signaling session enabling subsequent transmission or playing out of media packets containing media payloads over the media path; and

inserting a time stamp into the transmitted no-op media payload packets with the logic circuitry that identifies a non-zero amount of simulated media time for media content in the no-op media payload packets that is not actually encoded into the no-op media payload packets.

2. (Previously Presented) A method according to claim 1 including formatting the no-op media payload packets as a Real Time Protocol (RTP) media payload packet that is formatted as though it contains media content but that contains no media content and sending the no-op media payload packets during a Session Initiation Protocol (SIP) media call signaling session.

3. (Original) A method according to claim 1 generating a media path analysis report from the information generated from the transmitted no-op media payload packets.
4. (Original) A method according to claim 3 wherein the media path analysis report is a Real Time Control Protocol (RTCP) report.
5. (Original) A method according to claim 3 including setting a marker bit in the no-op media payload packets to initiate a receiver to immediately send back the media path analysis report.
6. (Previously Presented) A method according to claim 5 including determining whether or not to transmit a media stream over the media path according to when or if the media path analysis report is received after transmitting the no-op media payload packets with the set marker bit.
7. (Previously Presented) A method according to claim 3 including generating the media path analysis report without playing out contents of the no-op media payload packets.
8. (Previously Presented) A method according to claim 3 including:  
receiving multiple no-op media payload packets during the same media call signaling session; and  
generating the media path analysis report according to transmission information for all of the multiple no-op media payload packets.
- Cancel claim 9.
10. (Previously Presented) A method according to claim 1 including notifying a user of a media call according to the information associated with the transmission of the no-op media payload packets.
11. (Previously Presented) A network processing device, comprising:  
a processor configured to:

conduct an initial media call signaling session for establishing a media call and setting up a media path over a packet switched network;

send and/or receive one or more no-op media payload packets over the media path during the initial media call signaling session, the no-op media payload packets formatted as though the media packets contain media payloads but the no-op media payload packets formatted without media payloads;

selectively complete or terminate the initial media call signaling session according to information obtained from transmission of the no-op media payload packet during the initial media call signaling session, wherein successful completion of the initial media call signaling session enables subsequent transmission or playing out of media packets containing media payloads over the media path; and

insert a time stamp into the no-op media payload packets that identifies a non-zero amount of simulated media time for media content in the media payload that is not actually encoded into the media payload of the packets.

Cancel claim 12.

13. (Previously Presented) The network processing device according to claim 11 wherein the processor is configured to generate a Real Time Control Protocol (RTCP) report using the information obtained from transmission of the no-op media payload packets.

14. (Previously Presented) The network processing device according to claim 11 including a user interface configured to communicate with a device that initiates an Internet Protocol network connection for transmitting the media packets.

15. (Previously Presented) The network processing device according to claim 11 wherein the initial media call signaling session notifies a receiver that the no-op media payload packets are going to be used for analyzing the packet switched network.

16. (Previously Presented) The network processing device according to claim 15 wherein the processor is configured to generate a marker bit in one of the no-op media payload packets that causes the receiver to send back the information obtained from transmission of the no-op media payload packets.

17. (Previously Presented) The network processing device according to claim 11 wherein the processor is configured to send or receive the media packets according to a number of successfully transmitted no-op media payload packets and the jitter statistics for the no-op media payload packets.

18. (Currently Amended) A method for analyzing a media path in a packet switched network, comprising: ~~A tangible computer-readable storage medium encoded with computer-executable instructions, that, if executed by a network device, cause the network device to perform a method comprising:~~

initiating a Real Time Protocol (RTP) signaling session with a network processing device for establishing a media path for transporting RTP payload packets that contain media payloads;

sending multiple RTP payload packets with the network processing device during and within the RTP signaling session that are formatted as if the RTP payload packets contain a media payload but the RTP payload packets are formatted without media payloads and do not contain any media payload;

selectively completing or terminating the RTP signaling session with the network processing device according to information obtained by sending the RTP payload packets during the RTP signaling session, wherein successful completion of the RTP signaling session enables subsequent transmission or playing out of RTP packets containing media payloads over the media path; and

inserting a time stamp into the transmitted RTP payload packets with the network processing device that identifies a non-zero amount of simulated media time for media content in the RTP payload packets that is not actually encoded into the RTP payload packets.

19. (Currently Amended) The method ~~The tangible computer-readable storage medium~~ according to claim 18 including:

receiving multiple RTP payload packets that contain no media payload;

generating a Real Time Control Protocol (RTCP) report that includes media path information for the received RTP payload packets;

sending the RTCP report when one of the RTP payload packets is received that has a set marker bit; and

establishing a media stream according to the media path information in the RTCP report.

20. (Currently Amended) The method ~~The tangible computer-readable storage medium~~ according to claim 19 including delaying ringing a phone used for receiving a media stream until the RTCP report is received and indicates an acceptable media path for sending the media stream.

**REMARKS**


The Examiner has indicated that claims 18-20 would be allowable if their preambles were changed back to their previous form. The Examiner also indicated that claims 1 and 18 would be allowable if amended to overcome possible 35 USC 101 issues. Claims 1 and 18-20 have been amended as suggested by the Examiner and accordingly are in condition for allowance. The Examiner indicated that all other claims were in condition for allowance.

**Conclusion**

For the foregoing reasons, reconsideration and allowance of claims 1-8, 10-11, and 13-20 as amended is requested. The Examiner is encouraged to telephone the undersigned at (503) 224-2170 if it appears that an interview would be helpful in advancing the case.

Respectfully submitted,

STOLOWITZ FORD COWGER LLP

  
\_\_\_\_\_  
Stephen S. Ford  
Reg. No. 35,139

STOLOWITZ FORD COWGER LLP  
621 SW Morrison Street, Suite 600  
Portland, Oregon 97205

**Customer No. 73552**